



2025 PIONEER 520 SPECIFICATIONS*

ENGINE	
Engine Type	518cc liquid-cooled single-cylinder four-stroke
Bore And Stroke	96.0mm x 71.5mm
Compression Ratio	9.5:1
Valve Train	OHV; two valves per cylinder
Induction	Electronic fuel injection (PGM-FI), 36mm throttle body
DRIVE TRAIN	
Clutch	Automatic
Transmission	Five-speed automatic transmission with AT/MT modes
Driveline	Direct front and rear driveshafts
CHASSIS SUSPENSION BRAKES	
Front Suspension	Independent double-wishbone; 5.8-inch travel
Rear Suspension	Independent double-wishbone with preload adjustability; 5.9-inch travel
Front Brake	Dual 200mm hydraulic disc
Rear Brake	Single 170mm hydraulic disc
Front Tires	24 x 8-12
Rear Tires	24 x 10-12
DIMENSIONS	
Length	105.0 inches
Width	50.0 inches
Height	71.2 inches
Wheelbase	73.0 inches
Bed Capacity	450 pounds
Towing Capacity	1000 pounds
Ground Clearance	8.5 inches
Turning Radius	12.8 feet
Curb Weight	1058 pounds - Includes all standard equipment, required fluids and full tank of fuel.
Fuel Capacity	4.1 gallons, including 1.1-gallon reserve
OTHER	
Safety	Recommended for Drivers 16 years of age and older.
Available Colors	Hero Red, Slate Gray, TrueTimber® Atera Camo
Model ID	SXS520M2
FACTORY WARRANTY INFORMATION	
One Year Included	Transferable, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.

©2024 American Honda Motor Co., Inc. – Powersports Division