



2025 PIONEER 700 DELUXE SPECIFICATIONS*

ENGINE

Engine Type	675cc liquid-cooled OHV single-cylinder four-stroke
Bore And Stroke	102.0mm x 82.6mm
Compression Ratio	9.2:1
Induction	Fuel Injection (PGM-FI), 40mm throttle body
Valve Train	OHV; four valves per cylinder

DRIVE TRAIN

Clutch	Automatic
Transmission	Automotive-style automatic transmission with hydraulic torque converter
Driveline	Direct front and rear driveshafts

CHASSIS SUSPENSION BRAKES

Front Suspension	Independent double-wishbone; 7.9-inch travel
Rear Suspension	Independent double-wishbone; 9.1-inch travel
Front Brake	Dual 200mm hydraulic discs
Rear Brake	Single 170mm hydraulic disc
Front Tires	25 x 8-12
Rear Tires	25 x 10-12

DIMENSIONS

Length	114.8 inches
Width	59.9 inches
Height	77.6 inches
Wheelbase	76.8 inches
Bed Capacity	1000 pounds
Towing Capacity	1500 pounds
Ground Clearance	10.8 inches
Turning Radius	14.8 feet
Curb Weight	1,303 pounds - Includes all standard equipment, required fluids and full tank of fuel.
Fuel Capacity	8.1 gallons, including 1.5-gallon reserve

OTHER

Safety	Recommended for Drivers 16 years of age and older.
Available Colors	Hero Red, Black Forest Green
Model ID	SXS700M2D

FACTORY WARRANTY INFORMATION

One Year Included	Transferable, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.