



2026 PIONEER 700 DELUXE SPECIFICATIONS*

ENGINE	
Engine Type	675cc liquid-cooled single-cylinder four-stroke
Bore And Stroke	102.0mm x 82.6mm
Compression Ratio	9.2:1
Induction	Programmed Fuel-Injection system (PGM-FI); 40mm throttle body
Valve Train	OHV; four valves per cylinder
DRIVETRAIN	
Clutch	Automatic
Transmission	Automotive-style automatic transmission with hydraulic torque converter
Driveline	Direct front and rear driveshafts
CHASSIS SUSPENSION BRAKES	
Front Suspension	Independent double-wishbone; 7.9-inch travel
Rear Suspension	Independent double-wishbone; 9.1-inch travel
Front Brakes	Dual 200mm discs
Rear Brake	Single 170mm disc
Front Tires	25 x 8-12
Rear Tires	25 x 10-12
DIMENSIONS	
Length	114.8 inches
Width	59.9 inches
Height	77.6 inches
Wheelbase	76.8 inches
Bed Capacity	1000.0 pounds
Towing Capacity	1500.0 pounds
Ground Clearance	10.8 inches
Turning Radius	14.8 feet
Curb Weight	1,307 pounds (includes all standard equipment, required fluids and a full tank of fuel)
Fuel Capacity	8.1 gallons
OTHER	
Safety	Recommended for Drivers 16 years of age and older.
Available Colors	Hero Red, Black Forest Green
Model ID	SXS700M2D
Seating Capacity	2
FACTORY WARRANTY INFORMATION	
Duration	Transferable, one year included, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.

©2026 American Honda Motor Co., Inc. – Powersports Division