



## 2023 TALON 1000X-4 FOX LIVE VALVE SPECIFICATIONS\*

### ENGINE

Engine Type	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke
Bore And Stroke	92.0mm x 75.1mm
Compression Ratio	10:1
Valve Train	Unicam® SOHC; four valves per cylinder
Induction	Fuel Injection (PGM-FI); 46mm throttle body

### DRIVE TRAIN

Transmission	Six-speed automatic DCT
Driveline	Direct front and rear driveshafts

### CHASSIS SUSPENSION BRAKES

Front Suspension	Independent double-wishbone with FOX Live Valve shocks; 14.4-inch travel
Rear Suspension	4+ link trailing arm with FOX Live Valve shocks; 15.0-inch travel
Front Brake	Dual 250mm hydraulic discs
Rear Brake	Dual 250mm hydraulic discs
Front Tires	28 x 9-15
Rear Tires	28 x 11-15

### DIMENSIONS

Length	152.5 inches
Width	64.0 inches
Height	78.6 inches
Wheelbase	116.4 inches
Bed Capacity	299 pounds
Ground Clearance	12.8 inches
Turning Radius	21.7 feet
Curb Weight	1795 pounds for 49 states - Includes all standard equipment, required fluids and full tank of fuel.
Curb Weight	1797 pounds for CA models - Includes all standard equipment, required fluids and full tank of fuel.
Fuel Capacity	7.3 gallons, including 1.1-gallon reserve

### OTHER

Safety	Recommended for drivers 16 years of age and older.
Available Colors	Matte Navy Blue, Pearl Red
Model ID	SXS10S4XD
Emissions	Meets current California Air Resources Board (CARB) and EPA standards.

### FACTORY WARRANTY INFORMATION

Duration	One Year Included
Description	Transferable limited warranty; extended coverage available with a HondaCare® Protection Plan

\*All figures are preliminary and subject to change.

©2024 American Honda Motor Co., Inc. – Powersports Division