



## 2024 TALON 1000X FOX LIVE VALVE SPECIFICATIONS\*

ENGINE	
Engine Type	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke
Bore And Stroke	92.0mm x 75.1mm
Compression Ratio	10:1
Valve Train	Unicam® SOHC; four valves per cylinder
Induction	Fuel Injection (PGM-FI), 46mm throttle body
DRIVE TRAIN	
Transmission	Six-speed automatic Dual-Clutch Transmission (DCT) with high/low subtransmission; two drive modes with 2WD and 4WD; three shift modes (standard, sport, manual); paddle shifters
Driveline	Direct front and rear driveshafts
CHASSIS SUSPENSION BRAKES	
Front Suspension	Independent double-wishbone with FOX Live Valve shocks; 14.4-inch travel
Rear Suspension	4+ link trailing arm with FOX Live Valve shocks; 15.0-inch travel
Front Brake	Dual 250mm hydraulic discs
Rear Brake	Dual 250mm hydraulic discs
Front Tires	28 x 9-15
Rear Tires	28 x 11-15
DIMENSIONS	
Length	123.7 inches
Width	64.0 inches
Height	75.4 inches
Wheelbase	87.6 inches
Bed Capacity	299 pounds
Ground Clearance	12.8 inches
Turning Radius	17.7 feet
Curb Weight	1552 pounds for 49 states - Includes all standard equipment, required fluids and full tank of fuel.
Curb Weight	1554 pounds for CA models - Includes all standard equipment, required fluids and full tank of fuel.
Fuel Capacity	7.3 gallons, including 1.1-gallon reserve
OTHER	
Safety	Recommended for drivers 16 years of age and older.
Available Colors	Matte Navy Blue, Pearl Red
Model ID	SXS10S2XD
Emissions	Meets current California Air Resources Board (CARB) and EPA standards.
FACTORY WARRANTY INFORMATION	
Duration	One Year Included
Description	Transferable limited warranty; extended coverage available with a HondaCare® Protection Plan

\*All figures are preliminary and subject to change.

©2024 American Honda Motor Co., Inc. – Powersports Division