



2024 TALON 1000R-4 FOX LIVE VALVE SPECIFICATIONS*

ENGINE

Engine Type	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke
Bore And Stroke	92.0mm x 75.1mm
Compression Ratio	10:1
Valve Train	Unicam® SOHC; four valves per cylinder
Induction	Fuel Injection (PGM-FI); 46mm throttle body

DRIVE TRAIN

Transmission	Six-speed automatic Dual-Clutch Transmission (DCT) with high/low subtransmission. Two drive modes with 2WD and 4WD. Three shift modes (standard, sport, manual w/ paddle shifters).
Driveline	Direct front and rear driveshafts

CHASSIS SUSPENSION BRAKES

Front Suspension	Independent double-wishbone with FOX Live Valve shocks; 17.6-inch travel
Rear Suspension	4+ link trailing arm with FOX Live Valve shocks; 20.1-inch travel
Front Brake	Dual 250mm hydraulic discs
Rear Brake	Dual 250mm hydraulic discs
Front Tires	28 x 9-15
Rear Tires	28 x 11-15

DIMENSIONS

Length	152.2 inches
Width	68.1 inches
Height	79.0 inches
Wheelbase	118.7 inches
Bed Capacity	299 pounds
Ground Clearance	13.2 inches
Turning Radius	22.6 feet
Curb Weight	1843 pounds for 49 states - Includes all standard equipment, required fluids and full tank of fuel.
Curb Weight	1845 pounds for CA models - Includes all standard equipment, required fluids and full tank of fuel.
Fuel Capacity	7.3 gallons, including 1.1-gallon reserve

OTHER

Safety	Recommended for drivers 16 years of age and older.
Available Colors	Matte Navy Blue, Pearl Red
Model ID	SXS10S4RD
Emissions	Meets current California Air Resources Board (CARB) and EPA standards.

FACTORY WARRANTY INFORMATION

Duration	One Year Included
Description	Transferable limited warranty; extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.

©2024 American Honda Motor Co., Inc. – Powersports Division