2026 TALON 1000X-4 SPECIFICATIONS*

ENGINE	
Engine Type	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke
Bore And Stroke	92.0mm x 75.1mm
Compression Ratio	10.0:1
Valve Train	Unicam® SOHC; four valves per cylinder
Induction	Programmed Fuel-Injection system (PGM-FI); 46mm throttle body

DRIVETRAIN	
Transmission	Six-speed automatic Dual-Clutch Transmission (DCT)
Driveline	Direct front and rear driveshafts

CHASSIS SUSPENSION BRAKES	
Front Suspension	Independent double-wishbone with Showa® shocks; 14.6-inch travel
Rear Suspension	3-link trailing arm with Showa® shocks; 15.0-inch travel
Front Brakes	Dual 250mm discs
Rear Brakes	Dual 250mm discs
Front Tires	28 x 9-15
Rear Tires	28 x 11-15

DIMENSIONS	
Length	152.5 inches
Width	64.0 inches
Height	78.6 inches
Wheelbase	116.4 inches
Bed Capacity	297 pounds
Ground Clearance	12.8 inches
Turning Radius	21.7 feet
Curb Weight	1811 pounds (includes all standard equipment, required fluids and a full tank of fuel)
Fuel Capacity	7.7 gallons

OTHER	
Safety	Recommended for drivers 16 years of age and older.
Seating Capacity	4
Available Colors	Matte Forged Bronze, Pearl Red
Model ID	SXS10S4X
Emissions	Meets current California Air Resources Board (CARB) and EPA standards.

FACTORY WARRANTY INFORMATION	
Duration	Transferable, one-year included, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.

©2026 American Honda Motor Co., Inc. – Powersports Division