



DISCOVER WHAT A RECON CAN DO

If you're on a reconnaissance mission to find the best ATV value out there, make sure you take a long, hard look at the Honda FourTrax Recon. In a time when some other ATVs are getting bigger, more complex and more expensive, the Recon continues to deliver excellent performance and unsurpassed build quality in a package that's more maneuverable and less fatiguing than much of the competition. Its specially designed 250-class engine delivers plenty of low-rpm torque and power. Two versions let you choose from a conventional foot-shift ATV transmission or our Recon ES model offering Honda Electric Shift Program (ESP)—to shift you just push a pair of handlebar-mounted buttons. But make sure you pick a color you like (Avenger Red, Black Forest Green, or our new Krypton Green this year), because like every Honda ATV, your Recon is designed to last for years and years.




UTILITY ATVS ARE RECOMMENDED FOR RIDERS 16 YEARS AND OLDER. ATVS CAN BE HAZARDOUS TO OPERATE. FOR YOUR SAFETY, BE RESPONSIBLE. READ THE OWNER'S MANUAL. ALWAYS WEAR A HELMET, EYE PROTECTION AND PROTECTIVE CLOTHING. BE CAREFUL ON DIFFICULT TERRAIN. NEVER RIDE AFTER CONSUMING DRUGS OR ALCOHOL. ON PAVED SURFACES, ON PUBLIC ROADS, WITH PASSENGERS, OR AT EXCESSIVE SPEEDS. NO STUNT RIDING. RESPECT THE ENVIRONMENT WHEN RIDING. FourTrax® and Recon® are registered trademarks of Honda Motor Co., Ltd. ©2023 American Honda Motor Co., Inc.


2024 FourTrax Recon/ES



FourTrax Recon



FourTrax Recon ES



FEATURES & BENEFITS

SEMI-DRY-SUMP ENGINE DESIGN

Compact and lighter-weight, the Recon's semi-dry-sump and overhead valve designs create an engine that's not only shorter from top to bottom, but one that enhances handling by lowering the center of gravity while also allowing for better ground clearance.

LONGITUDINAL ENGINE LAYOUT

By orienting the crankshaft front to back in the chassis in our ATV and side-by-side engines, we route the flow of power straight to the wheels without any unnecessary right-angle detours, reducing powertrain friction and putting more grunt to the ground.

ELECTRIC SHIFT PROGRAM (ESP)

Shifting between gears should always be this easy. With Honda's available unique ESP system (ES models only), upshifting and downshifting is as simple and fast as pushing one of two handlebar-mounted buttons. ESP is also a bonus when riding in heavy or mud/snow-covered boots.

SHAFT DRIVE

Clean, efficient, proven, low-maintenance. Shaft drive is the perfect choice for a machine like this, and for riders who pile on the miles. You never have to worry about lubrication or adjustment out on the trail.





2024 FourTrax Recon/ES



FourTrax Recon

FourTrax Recon ES

ENGINE TYPE	229cc air-cooled OHV longitudinally mounted single-cylinder four-stroke	229cc air-cooled OHV longitudinally mounted single-cylinder four-stroke
BORE AND STROKE	68.5mm x 62.2mm	68.5mm x 62.2mm
INDUCTION	22mm piston-valve carburetor	22mm piston-valve carburetor
VALVE TRAIN	OHV; two valves per cylinder	OHV; two valves per cylinder
COMPRESSION RATIO	9.2:1	9.2:1
TRANSMISSION	Five-speed ATV-style semi-automatic with reverse	Five-speed with reverse; electric shifting
DRIVELINE	Direct rear driveshaft	Direct rear driveshaft
FRONT SUSPENSION	Independent double-wishbone; 5.1-inch travel	Independent double-wishbone; 5.1-inch travel
REAR SUSPENSION	Swingarm with single shock; 4.9-inch travel	Swingarm with single shock; 4.9-inch travel
FRONT BRAKES	Dual sealed 130mm drums	Dual sealed 130mm drums
REAR BRAKES	Sealed 140mm drum	Sealed 140mm drum
FRONT TIRES	22 x 7-11	22 x 7-11
REAR TIRES	22 x 10-9	22 x 10-9
WHEELBASE	44.5 inches	44.5 inches
LENGTH	75.0 inches	75.0 inches
HEIGHT	42.1 inches	42.1 inches
SEAT HEIGHT	31.2 inches	31.2 inches
GROUND CLEARANCE	6.0 inches	6.0 inches
CURB WEIGHT	437 pounds (Includes all standard equipment, required fluids and full tank of fuel)	443 pounds (Includes all standard equipment, required fluids and full tank of fuel)
FUEL CAPACITY	2.4 gallons, including 0.6-gallon reserve	2.4 gallons, including 0.6-gallon reserve
FRONT RACK CAPACITY	33 pounds	33 pounds
REAR RACK CAPACITY	66 pounds	66 pounds
TOWING CAPACITY	500 pounds	500 pounds
TURNING RADIUS	8.5 feet	8.5 feet